

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** 090159-42421 Glass Clnr Plus P 3033

**Other means of identification**

**Product code** 1000019699

**Recommended use** CLEANER

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name** IMPROVED CHEMICAL LTD.

**Address** 5762 Highway 7 East  
Markham, Ontario L3P 7Y4  
Canada

**Telephone** General Assistance 1-416-877-4516

**E-mail** Not available.

**Emergency phone number** Emergency - Outside US 1-952-852-4646  
Emergency - US 1-866-836-8855

**Supplier** Not available.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1

**Health hazards** Serious eye damage/eye irritation Category 2

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Causes serious eye irritation.

### Precautionary statement

**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection.

**Response** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Storage** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3  
Hazardous to the aquatic environment, long-term hazard Category 3

**Other hazards** None known.

**Supplemental information** None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Isopropyl Alcohol		67-63-0	3 - 7
2-Butoxyethanol		111-76-2	1 - 5

Chemical name	Common name and synonyms	CAS number	%
Isobutane		75-28-5	1 - 5
Ammonium Hydroxide		1336-21-6	0.1 - 1
Propane		74-98-6	0.1 - 1
Other components below reportable levels			60 - 100

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
<b>Most important symptoms/effects, acute and delayed</b>	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Not available.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
<b>Environmental precautions</b>	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	97 mg/m3
		20 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	984 mg/m3
		400 ppm
	TWA	492 mg/m3
		200 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm

#### Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Isobutane (CAS 75-28-5)	TWA	800 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
	TWA	200 ppm

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	97 mg/m3
		20 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	1230 mg/m3
		500 ppm
	TWA	983 mg/m3
		400 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**Other**

Wear suitable protective clothing.

**Respiratory protection**

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Gas.

**Form**

Aerosol.

**Color**

Not available.

**Odor**

Not available.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

212 °F (100 °C) estimated

**Flash point**

-99.4 °F (-73.0 °C) PROPELLANT estimated

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not available.

**Upper/lower flammability or explosive limits**

<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.

**Vapor pressure** Not available.

**Vapor density** Not available.

**Relative density** Not available.

**Solubility(ies)**

**Solubility (water)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** Not available.

**Decomposition temperature** Not available.

**Viscosity** Not available.

**Other information**

**Explosive properties** Not explosive.

**Oxidizing properties** Not oxidizing.

**Specific gravity** 0.963 estimated

**10. Stability and reactivity**

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** Hazardous polymerization does not occur.

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

**Hazardous decomposition products** No hazardous decomposition products are known.

**11. Toxicological information****Information on likely routes of exposure**

**Inhalation** No adverse effects due to inhalation are expected.

**Skin contact** 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

**Information on toxicological effects****Acute toxicity**

Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-2)		
<u>Acute</u>		
<b>Dermal</b> LD50	Guinea pig	7.3 ml/kg, 4 Days
		0.23 ml/kg, 24 Hours
	Rabbit	435 mg/kg, 24 Hours
		0.68 ml/kg, 24 Hours

Components	Species	Test Results
		0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
<b>Inhalation</b>		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
<b>Oral</b>		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1414 mg/kg
	Mouse	1519 mg/kg
	Rat	1746 mg/kg
Isobutane (CAS 75-28-5)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Isopropyl Alcohol (CAS 67-63-0)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	16.4 ml/kg, 24 Hours
<b>Inhalation</b>		
LC50	Rat	> 10000 ppm, 6 Hours
<b>Oral</b>		
LD50	Rat	5.84 g/kg
Propane (CAS 74-98-6)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

#### Respiratory or skin sensitization

##### Canada - Alberta OELs: Irritant

2-Butoxyethanol (CAS 111-76-2) Irritant

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

#### Carcinogenicity

##### ACGIH Carcinogens

2-Butoxyethanol (CAS 111-76-2) A3 Confirmed animal carcinogen with unknown relevance to humans.

Isopropyl Alcohol (CAS 67-63-0) A4 Not classifiable as a human carcinogen.

**Canada - Manitoba OELs: carcinogenicity**

2-BUTOXYETHANOL (EGBE) (CAS 111-76-2)

2-PROPANOL (CAS 67-63-0)

Confirmed animal carcinogen with unknown relevance to humans.

Not classifiable as a human carcinogen.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

2-Butoxyethanol (CAS 111-76-2)

3 Not classifiable as to carcinogenicity to humans.

**Reproductive toxicity**

This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure**

Not classified.

**Specific target organ toxicity - repeated exposure**

Not classified.

**Aspiration hazard**

Not likely, due to the form of the product.

**Chronic effects**

May be harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

**12. Ecological information****Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
2-Butoxyethanol (CAS 111-76-2)			
<b>Aquatic</b>			
Fish	LC50	Inland silverside ( <i>Menidia beryllina</i> )	1250 mg/l, 96 hours
Ammonium Hydroxide (CAS 1336-21-6)			
<b>Aquatic</b>			
Crustacea	EC50	Daphnia	0.66 mg/L, 48 Hours
Fish	LC50	Western mosquitofish ( <i>Gambusia affinis</i> )	15 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-63-0)			
<b>Aquatic</b>			
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	> 1400 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability**

No data is available on the degradability of this product.

**Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

2-Butoxyethanol	0.83
Isobutane	2.76
Isopropyl Alcohol	0.05
Propane	2.36

**Mobility in soil**

No data available.

**Other adverse effects**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations****Disposal instructions**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations**

Dispose in accordance with all applicable regulations.

**Hazardous waste code**

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging**

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

**14. Transport information****TDG**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	D
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. This product meets the exemption requirements and may be shipped as a limited quantity.

**IATA**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

**IMDG**

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable.

**IATA; IMDG; TDG**





## 15. Regulatory information

### Canadian regulations

#### Controlled Drugs and Substances Act

Not regulated.

#### Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### Greenhouse Gases

Not listed.

#### Precursor Control Regulations

Not regulated.

### International regulations

#### Stockholm Convention

Not applicable.

#### Rotterdam Convention

Not applicable.

#### Kyoto protocol

Not applicable.

#### Montreal Protocol

Not applicable.

#### Basel Convention

Not applicable.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other Information

**Issue date** 02-14-2018

**Version #** 01

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision information** Product and Company Identification: Alternate Trade Names